

12W AC/DC SMPS




DESCRIPTION


- ★ Wide input : AC85~264V & DC100~375V
- ★ Output short circuit, over-current protection
- ★ Compact size, high power density
- ★ I/O isolation test voltage 3k VAC
- ★ Low ripple & noise
- ★ RoHS Compliant
- ★ Industrial grade, high reliability
- ★ Three-year quality assurance

NQ12-AxxSN series is one of Nyboxing's highly efficient green power AC-DC Converter series. They feature ultra-wide wide input range accepting either AC or DC voltage, high efficiency, low power consumption and Class II reinforced insulation.

Dimensions



Front view



Side view

PIN	Function	
	AC IN	DC IN
1	N	DC
2	L	DC
3	+Vo	+Vo
4	-Vo	-Vo

Note:
Unit:mm[inch]
Pin diameter tolerances: $\pm 0.20[\pm 0.008]$
General tolerances: $\pm 0.50[\pm 0.020]$

Selection Guide

Part No.	Output Power	Nominal Output Voltage and Current	Efficiency at 230VAC (%) Typ.	Capacitive Load (μ F) Max.	Dimensions (LxWxH)
NQ12-A03SN	6.6W	3.3V/2000mA	75%	1000 μ F	
NQ12-A05SN	10W	5V/2000mA	78%	1000 μ F	
NQ12-A09SN		9V/1330mA	80%	820 μ F	
NQ12-A12SN		12V/1000mA	81%	680 μ F	36.0x22.0x17.0mm
NQ12-A15SN	12W	15V/800mA	82%	470 μ F	
NQ12-A24SN		24V/500mA	84%	330 μ F	

Input Specifications

Item	Operating Conditions	Min	Typ	Max
Input Voltage Range	AC input	85VAC	--	264VAC
	DC input	100VDC	--	375VDC

Input Frequency	47Hz	--	63Hz
Stand-by Power Consumption	--	0.1W	--
Input Current 115VAC 230VAC	--	200mA	--
	--	100mA	--

Output Specifications



Item	Operating Conditions	Min	Typ	Max
Output Voltage Accuracy		--	±1%	--
Line Regulation	Full load	--	±1.5%	--
Load Regulation	10%~100% Load	--	±2.5%	--
Ripple & Noise* (peak-to-peak value)	20MHz bandwidth 3.3V/5V Output	--	150mV	--
	Other output	--	100mV	--
Short Circuit Protection		Hiccup, continuous, self-recovery		
Over-current Protection		≥110%Io		
Minimum Load		0	--	--
Start delay time		--	500ms	--
Hold-up Time		--	10ms	--
Minimum Load		0%	--	--

Note: * The "parallel cable" method is used for Ripple and noise test, please refer to AC-DC Converter Application Notes for specific information.

General Specifications

Item	Operating Conditions	Min	Typ	Max
Isolation	Input-Output, Test for 1min	--	3000VAC	--
Operating Temperature		-40°C	--	+70°C
Storage Temperature		-40°C		+105°C
Storage Humidity		--	--	95%RH
Working frequency		--	65KHz	--
MTBF	MIL-HDBK-217F, 25°C		215,000h	

Product Characteristic Curve



Design Reference

1 Typical application




Fig. 1: Typical circuit diagram

Note

We recommend using an electrolytic capacitor with high frequency, and low ESR rating for C1 (refer to manufacturer's datasheet). Choose a Capacitor voltage rating with at least 20% margin, in other words not exceeding 80%. C2 is a ceramic capacitor used for filtering high-frequency noise.

2 EMC compliance recommended circuit




Fig 2: EMC application circuit with higher requirements

3 Input part: parameter recommendation

Component	Recommended value
FUSE	2A/250V slow-blow required
R1	5D-9
MOV	471KD10
CX	0.1μF/275VAC
L1	470μH
NF	10mH-30mH
CY1,CY2	1000pF/250V

4 Output part: parameter recommendation

Output Voltage	3.3V	5V	9V	12V	15V	24V
C1	220μF/10V		220μF/25V		68μF/35V	
C2			1μF/50V			

Safety precautions

- If the product is not operated within the required load range, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
- Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^\circ\text{C}$, humidity < 75% with nominal input voltage and rated output load;
- All index testing methods in this datasheet are based on our Company's corporate standards;
- We can provide product customization service, please contact our technicians directly for specific information;
- For more product information, please visit our official website (www.gzny-boxing.com) or email us (sales@gzny-boxing.com).